

1500EV

Portable VSI Plant



Impact Crusher - VSI

- Fully replaceable bolt on liners for tub, pedestal, and lid
- Feed box with externally adjustable feed tube
- 8 1/2" (215mm) feed diameter
- Hinged access doors in lid
- Roller bearing pedestal assembly
- 5 HP pedestal lubrication system with electric pump
- Oil alarm and cooling system
- Vibration monitor
- Application specific internal configurations
- Max feed size rotor = 2" (51mm)
- Max feed size shoe table = 2" (51mm)
- Accelerator speed = 1,200 to 2,000 RPM

End Delivery Conveyor

- 42" fixed height with full spill boards and cover
- Belt cleaner and discharge hood
- Screw take-up belt tension
- 10hp TEFC electric motor

Chassis

- 30-TEC frame with single rear axle
- Rear crib legs and king pin support
- Four 11.00 x 22.5 dual mounted tires
- Air brakes, travel lights, mudflaps
- Service platforms with ladder
- Crusher discharge chute

Options

- Hard Parts (H) / Standard configuration including 3, 4, or 5 shoe impellor table and anvil cluster ring
- Semi-Autogenous (SA) configuration including 3 port rotor and anvil cluster ring
- Autogenous (A) configuration including 3 port rotor and hybrid rock shelf with anvils
- V-belt drive for electric motor with motor mount, crusher sheave, motor sheave, and v-belts
- 150 HP TEFC electric motor at 1,800 RPM
- 200 HP TEFC electric motor at 1,800 RPM
- Starter and 60' of cable for electric motor and 5 HP lube pump in NEMA-12 panel box
- Variable Frequency Drive (VFD) for crusher motor speed control
- Hydra arm lid removal system includes power lift and manual rotate for service
- Lube oil tank heater
- Belt scale
- Mid-point dust suppression spray bar
- Remote grease for conveyor head and tail pulley
- Transport bracket for spare / optional internal configuration components

Physical/Operating Characteristics

Dimension	Standard	Metric
Operating Length	35' 6"	10.8m
Travel Length	35' 6"	10.8m
Operating Height	12' 11"	3.9m
Travel Height	11' 4"	3.5m
Ground Clearance	15"	0.2m
Total Weight (150 HP motor)	30,460lb	13,816kg
End Delivery Conveyor	4,030lb	1,828kg
Feed Hopper	250lb	114kg
Operating Width (approx panel)	13' 1"	4.0m

Dimension	Standard	Metric
Travel Width	10' 10"	3.3m
Feed Height	12' 11"	3.9m
Discharge Height	6' 3"	1.9m
Service Width (lid open)	14' 8"	4.5m
Service Height (lid open)	14' 1"	4.3m
Basic Motor Controls & Panel	500lb	227kg
150 HP Electric Motor & Mount	2,900lb	1,315kg
200 HP Electric Motor & Mount	3,500lb	1,587kg